

Zware "Pari" klem - Inbus M8
308-02

<u>Minimale Diameter</u>	<u>Maximale diameter</u>	<u>Bandbreedte</u>	<u>Max aandraai moment</u>	<u>Art. nummer FlexInd</u>
100 mm	110 mm	24 mm	25 Nm	308-02-110
105 mm	115 mm	24 mm	25 Nm	308-02-115
110 mm	120 mm	24 mm	25 Nm	308-02-120
115 mm	125 mm	24 mm	25 Nm	308-02-125
120 mm	130 mm	24 mm	25 Nm	308-02-130
125 mm	135 mm	24 mm	25 Nm	308-02-135
130 mm	140 mm	24 mm	25 Nm	308-02-140
135 mm	145 mm	24 mm	25 Nm	308-02-145
140 mm	150 mm	24 mm	25 Nm	308-02-150
145 mm	155 mm	24 mm	25 Nm	308-02-155
150 mm	160 mm	24 mm	25 Nm	308-02-160
155 mm	165 mm	24 mm	25 Nm	308-02-165
160 mm	170 mm	24 mm	25 Nm	308-02-170
165 mm	175 mm	24 mm	25 Nm	308-02-175
170 mm	180 mm	24 mm	25 Nm	308-02-180
180 mm	190 mm	24 mm	25 Nm	308-02-190
190 mm	200 mm	24 mm	25 Nm	308-02-200
200 mm	210 mm	24 mm	25 Nm	308-02-210
210 mm	220 mm	24 mm	25 Nm	308-02-220
220 mm	230 mm	24 mm	25 Nm	308-02-230
230 mm	240 mm	24 mm	25 Nm	308-02-240
240 mm	250 mm	24 mm	25 Nm	308-02-250
250 mm	260 mm	24 mm	25 Nm	308-02-260
260 mm	270 mm	24 mm	25 Nm	308-02-270
270 mm	280 mm	24 mm	25 Nm	308-02-280
280 mm	290 mm	24 mm	25 Nm	308-02-290
290 mm	300 mm	24 mm	25 Nm	308-02-300
300 mm	310 mm	24 mm	25 Nm	308-02-310
310 mm	320 mm	24 mm	25 Nm	308-02-320
320 mm	330 mm	24 mm	25 Nm	308-02-330