

// 2660A



**Air seeder - PVC**

**Construction:** transparent PVC - abrasion and ozone resistant.  
**Reinforcement:** black shock resistant rigid PVC.  
**Application:** agricultural seed transfer in "Air-Flo" seeding equipments.  
**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

| ↔    |        | ↔  |    | ↕   |     | ↕   |     | ⤴     |       | ⚖  |       |       |
|------|--------|----|----|-----|-----|-----|-----|-------|-------|----|-------|-------|
| mm   | in     | mm | in | bar | psi | bar | psi | mm    | in    | %  | kg/m  | lb/ft |
| 25,0 | 1"     |    |    | 8   | 120 | 24  | 350 | 113,0 | 4,45  | 70 | 0,295 | 0,20  |
| 32,0 | 1 1/4" |    |    | 7   | 100 | 21  | 300 | 144,0 | 5,67  | 70 | 0,395 | 0,27  |
| 38,0 | 1 1/2" |    |    | 6   | 90  | 18  | 270 | 171,0 | 6,73  | 70 | 0,515 | 0,35  |
| 45,0 | 1 3/4" |    |    | 6   | 90  | 18  | 270 | 203,0 | 7,99  | 70 | 0,675 | 0,46  |
| 51,0 | 2"     |    |    | 5   | 75  | 15  | 225 | 230,0 | 9,06  | 70 | 0,765 | 0,52  |
| 63,0 | 2 1/2" |    |    | 5   | 75  | 15  | 225 | 284,0 | 11,18 | 70 | 1,190 | 0,80  |
| 76,0 | 3"     |    |    | 5   | 75  | 15  | 225 | 342,0 | 13,46 | 70 | 1,520 | 1,03  |

// 702AA



**Air seeder**

**Tube:** black conductive NR.  
**Reinforcement:** high tensile textile cords with embedded steel helix wire.  
**Cover:** black NBR/PVC - oil, heat, abrasion and ozone resistant.  
**Application:** agricultural seed transfer in "Air-Flo" seeding equipments.  
**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

| ↔    |        | ↔     |      | ↕   |     | ↕   |     | ⤴     |       | ⚖   |       |       |
|------|--------|-------|------|-----|-----|-----|-----|-------|-------|-----|-------|-------|
| mm   | in     | mm    | in   | bar | psi | bar | psi | mm    | in    | %   | kg/m  | lb/ft |
| 32,0 | 1 1/4" | 43,00 | 1,69 | 10  | 150 | 30  | 450 | 128,0 | 5,04  | 100 | 0,880 | 0,60  |
| 38,0 | 1 1/2" | 49,00 | 1,93 | 10  | 150 | 30  | 450 | 152,0 | 5,98  | 100 | 1,000 | 0,68  |
| 45,0 | 1 3/4" | 56,00 | 2,20 | 10  | 150 | 30  | 450 | 180,0 | 7,09  | 100 | 1,190 | 0,80  |
| 51,0 | 2"     | 62,00 | 2,44 | 10  | 150 | 30  | 450 | 204,0 | 8,03  | 100 | 1,330 | 0,90  |
| 63,0 | 2 1/2" | 76,00 | 2,99 | 10  | 150 | 30  | 450 | 252,0 | 9,92  | 90  | 2,020 | 1,36  |
| 76,0 | 3"     | 89,00 | 3,50 | 10  | 150 | 30  | 450 | 304,0 | 11,97 | 90  | 2,410 | 1,62  |